

Luxtek[®]






LED Retrofit Lamps Standard & Globe series

Technical Advantages

- Long lifespan
- High luminous efficacy
- High energy efficiency
- High colour rendering
- Mercury free
- Zero UV emission
- Save 80-90% energy compare with incandescent bulbs

Product features

- Direct replacement of incandescent bulbs
- Various colour temperatures available
- Excellent heat disperse
- Dimmable version available



LG45	
E14	Ø45 x 78H mm
B15	Ø45 x 77H mm
E27	Ø45 x 70H mm
B22	Ø45 x 69H mm
LA60	
E27	Ø59 x 105H mm
B22	Ø59 x 104H mm
LA67	
E27	Ø67 x 125H mm
B22	Ø67 x 124H mm



Tolerance of product dimension Length \pm 2mm / Diameter \pm 0.5mm

G45
A60 / A67



Non-dimmable version

Model No.	Energy Class	Lumen	Wattage	Product Photo	Incandescent Equivalent	Colour Temperature	Lifetime	CRI	Voltage	Light Distribution	Base
LG45	A+	300 lm	4W	1	25W	2700 / 3000 / 4000 / 6500 K	15000 hrs	\geq 80	220~240V	165°	E27 / B22 E14 / B15
LA60	A+	300 lm	4W	2	25W	2700 / 3000 / 4000 / 6500 K	15000 hrs	\geq 80	220~240V	165°	E27 / B22
		500 lm	6W	2	40W						
		810 lm	10W	2	60W						
LA67	A+	1055 lm	13W	3	75W	2700 / 3000 / 4000 / 6500 K	15000 hrs	\geq 80	220~240V	165°	E27 / B22

Dimmable version

Model No.	Energy Class	Lumen	Wattage	Product Photo	Incandescent Equivalent	Colour Temperature	Lifetime	CRI	Voltage	Light Distribution	Base
LA60 Dim	A+	300 lm	4W	2	25W	2700 / 3000 / 4000 / 6500 K	15000 hrs	\geq 80	220~240V	165°	E27 / B22
		470 lm	6W	2	40W						
LA67 Dim	A+	810 lm	10W	3	65W	2700 / 3000 / 4000 / 6500 K	15000 hrs	\geq 80	220~240V	165°	E27 / B22